



## FEATURES:

- Backup time of 48 hours without main power on one 180 liter cylinder of LN2 at -60°C set point.
- The battery status indicator warns of a disconnected or low battery condition.
- Independent user-programmable controls for system alarm, LN2 injection temperature and on/off times.
- Visible and audible indicators for system status.
- Programmable alarm delay available to minimize nuisance or false alarms.
- Relay contact output for central alarm systems or automatic dialers.
- Door safety interlock switch prevents LN2 injection while freezer is being accessed.

The Model CA5000-N freezer back-up alarn system is a unique combination of field proven, ultra-reliable alarm systems and a LN2 injection system; providing security for your products to ultra-low temperatures.

It offers user-programmable alarm and control set points and alarm delay times. Parameters are stored in non-volatile memory and are maintained even when power is lost.

When a malfunction occurs and the freezer warms above the user-defined set point, an alarm sounds with flashing red LED. If the freezer continues to warm, then a user-defined amount of LN2 is injected into the freezer, quickly recovering the set point temperature.

## Custom programming and packaging can be provided.

PO Box 516, Dover New Hampshire 03821 U.S. Toll Free (866) 496-9424 Phone (603) 749-9424 • Fax (603) 749-9433 *E-mail:* sales@hampshirecontrols.com



# Model CA5000-N LN2 Freezer Backup Alarm System Detailed Specifications



BATTERY-VALVE-MODULE (BVM)

#### Power Requirements:

Includes Universal Power Supply, 120-240V/50-60 Hz UL listed Supplies 15VDC to BVM

### Mechanical:

BVM Box with handle = 6.25" W x 5" H x 15.625" D Control Alarm Box = Case is black bakelite, 5" W x 4.25" H x 1.75" D

#### Weight:

BVM Box = 18 poundsControl Alarm Box = 2 pounds

Temperature Range:  $-200^{\circ}$  C to  $+50^{\circ}$  C

Backup Temperature Range: -150° C to -40° C

Resolution: 1° C

Accuracy:  $\pm 2^{\circ} C$ 

Sensor: Type "T" Thermocouple with 10' lead

Battery: 12VDC 12Ah sealed lead-acid rechargeable

Relay Output: SPDT NO/NC dry contact, 30VDC/1A max. (non-inductive)

There is a one-year warranty on all Hampshire Controls products.

# Hampshire Controls Corp. is a Woman Owned Small Business

## About Our Company

Started in 1975, Hampshire Controls provides standard and custom designed electronics to the biomedical and industrial markets. In addition to the CA5000-N LN2 Freezer Backup Alarm System, other products include:

- Model 140 Single Probe Temperature Monitor
- Model MPS Multi-Point Monitor
- Alert Central Monitoring System (AMS)
- Model LD-200 LN2 Level Detector/Alarm
- Liquid CO2 Backup Control/Alarm for Freezers
- Line Voltage Controls

- Custom Microprocessor Assemblies
- Model ADM Alarm Delay Module
- Regulated Output Phase Control
- Custom AC Motor Phase Controls
- Air Flow Monitors
- Model TC-12 Rapid Response TempCheck

PO Box 516, Dover New Hampshire 03821 U.S. Toll Free (866) 496-9424 Phone (603) 749-9424 • Fax (603) 749-9433 *E-mail:* sales@hampshirecontrols.com

www.hampshirecontrols.com

MADE IN U.S.A

